#### SPECIAL CONSOLIDATED CHECKLIST

for the Wood Preserving Listings as of June 30, 1997

#### Notes:

- 1) This checklist consolidates the changes to the Federal code addressed by the following Wood Preserving Listings checklists:
- Revision Checklist 82 [55 FR 50450 (December 6, 1990)];
- Revision Checklist 91 [56 FR 27332 (June 13, 1991)];
- Revision Checklist 92 [56 FR 30192 (July 1, 1991)];
- Revision Checklist 101 [57 FR 5859 (February 18, 1992)]; and
- Revision Checklist 120 [57 <u>FR</u> 61492 (December 24, 1992)].

On June 29, 1995, EPA published a final rule removing provisions from the Code of Federal Regulations that are no longer legally in effect (see Revision Checklist 144; 60 <u>FR</u> 33912). While Revision Checklist 144 is not a Wood Preserving Listing checklist, it is noted in the checklist column of this consolidated WPL checklist because it corrects an error regarding the footnote following the table in §261.31(a). No final rules were promulgated between June 29, 1995 and June 30, 1997, that affected the Wood Preserving Listing. Therefore, this consolidated checklist is identical to that of June 30, 1996.

- 2) This consolidated checklist adds, to the list of wastes from non-specific sources, three broad categories of wastes from wood preserving processes that use chlorophenolic, creosote, and/or inorganic (arsenical and chromium) preservatives. These wastes, F032, F034 and F035, include wastewaters, process residuals, preservative drippage and spent formulations. The listing of F032 and the permitting and interim status standards applicable to drip pads handling this waste are promulgated pursuant to HSWA. The listings of F034 and F035, the permitting and interim standards for drip pads that handle F034 and F035 wastes, and the addition of a test method to Appendix III of Part 261 are non-HSWA provisions. EPA will implement the addition of F032 to the list of hazardous wastes from non-specific sources in authorized States until the States modify their programs and such modifications are approved by EPA. The non-HSWA requirements are applicable only in those States that do not have interim or final authorization. In authorized States, the non-HSWA requirements will not be applicable until the States revise their programs to adopt equivalent requirements under State law, unless the wastes are designated as hazardous due to the Toxicity Characteristic, which would allow an owner or operator to comply with the drip pad standards administered under Federal law.
- 3) Note that double lines are used on the checklists to indicate the beginning and ending of optional provisions with subparagraphs or requirements that must all be adopted if the optional provision is adopted.

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	PART 26	60 - HAZAR	DOUS WASTE MAN	AGEMENT SYST	EM: G	ENERAL	ı	
			SUBPART B - DEI	FINITIONS				
	DEFINITIONS							
	add "drip pad" in alphabetical order	82	260.10					
	PART 2	61 - IDENT	IFICATION AND LIS	TING OF HAZAI	RDOUS	WASTE		
			SUBPART A - G	ENERAL				
1	EXCLUSIONS							
†	Spent Wood Preserving Sc	olutions and V	Wastewaters					
	add new paragraph which excludes as a solid waste spent wood preserving solutions that have been reclaimed and are reused for their original intended purpose	82,92	261.4(a)(9)(i)					
	add new paragraph which excludes as a solid waste wastewaters from the wood preserving process that have been reclaimed and are reused to treat wood	92	261.4(a)(9)(ii)					
2	HAZARDOUS WASTES	FROM NO	N-SPECIFIC SOURCE	ES				
	add the waste codes "F032", "F034" and "F035" in alphanumeric order to list as shown below:	82,†91, †120	261.31(a)/table					

							STATE A	NALOG IS:	
FEDERAL REQUIREMENTS		CHECKLIST REFERENCE	FEDERAL RCI	RA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
Industry and EPA hazardous waste No.				Hazardo	us waste			Haza cod	
*	*		*	*	*		*		
F032	prod forn cod was and This	cess residuals, peesses generate nulations (excepted deleted in accestes that are other where the genes listing does no	oreservative drip d at plants that t potentially cro ordance with § erwise currently erator does not t include K001 I	opage, and spondered currently use ses-contaminate 261.35 of this regulated as lessume or initiate cottom sedimes	nto contact with process ent formulations from wo or have previously used ed wastes that have have chapter or potentially or nazardous wastes (i.e., ate use of chlorophenolient sludge from the treat use creosote and/or pe	ood presend chlorophe did the F032 contain F034 or F0 formulation of the formulation of t	ving nolic waste minated 035), ons).	(T	)
F034	prod prod K00	cess residuals, p cesses generate 11 bottom sedim	preservative drip ed at plants that ent sludge from	ppage, and spouse creosote the treatment	nto contact with process ent formulations from w formulations. This listin of wastewater from wo henol.	ood preser g does not	ving include	(T)	)
F035	F035 Wastewaters (except those that have not come into contact with process contaminants), process residuals, preservative drippage, and spent formulations from wood preserving processes generated at plants that use inorganic preservatives containing arsenic or chromium. This listing does not include K001 bottom sediment sludge from the treatment of wastewater from wood preserving processes that use creosote and/or pentachlorophenol.  * * * * * * * * * * * * * * * * * * *						(Т	)	
remove administrative stay		†91,120, 144	261.31(a)/	footnote-					

4

						STATE ANALOG IS:		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	DELETION OF CERTAIN REPLACEMENT	N HAZARD	OUS WASTE CODES	FOLLOWING E	QUIPMI	ENT CLE	ANING	AND
	wastes from wood preserving processes at plants that do not resume or initiate use of chlorophenolic preservatives will not meet the listing definition of F032 once the 261.35(b) and (c) requirements are met; wastes may continue to meet another hazardous waste listing description or exhibit one or more characteristics	82	261.35(a)					
5	generators must either clean or replace all specified process equipment that may have come into contact with chlorophenolic formulations or constituents	82,92	261.35(b)					
	generators shall do one of the following:	82,92	261.35(b)(1)					
	prepare and follow an equipment cleaning plan; clean equipment in accordance with 261.35	92	261.35(b)(1)(i)					
	prepare and follow an equipment replacement plan; replace equipment in accordance with 261.35	92	261.35(b)(1)(ii)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
6	document cleaning and replacement in accordance with 261.35, carried out after termination of use of chlorophenolic preservatives	92	261.35(b)(1)(iii)					
	cleaning requirements	82,92	261.35(b)(2)					
	prepare and sign a written equipment cleaning plan that describes:	92	261.35(b)(2)(i)					
	equipment to be cleaned	92	261.35(b)(2)(i)(A)					
	how equipment will be cleaned	92	261.35(b)(2)(i)(B)					
	solvent to be used in cleaning	92	261.35(b)(2)(i)(C)					
	how solvent rinses will be tested	92	261.35(b)(2)(i)(D)					
	how cleaning residues will be disposed	92	261.35(b)(2)(i)(E)					
	equipment must be cleaned as follows:	92	261.35(b)(2)(ii)					
	remove all visible residues from process equipment	92	261.35(b)(2)(ii)(A)					
	rinse with appropriate solvent until no dioxin or dibenzofuran detection in final solvent rinse	92	261.35(b)(2)(ii)(B)					
	analytical requirements	92	261.35(b)(2)(iii)					
	test rinses as per SW-846, Method 8290	92	261.35(b)(2)(iii)(A)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
"not detected" defined	92	261.35(b)(2)(iii)(B)					
generator manages cleaning process residues as F032 waste	92	261.35(b)(2)(iv)					
replacement requirements	82,92	261.35(b)(3)					
prepare and sign written equipment replacement plan that describes:	92	261.35(b)(3)(i)					
equipment to be replaced	92	261.35(b)(3)(i)(A)					
how equipment will be replaced	92	261.35(b)(3)(i)(B)					
how equipment will be disposed	92	261.35(b)(3)(i)(C)					
generator must manage discarded equipment as F032 waste	92	261.35(b)(3)(ii)					
documentation requirements	92	261.35(b)(4)					
document previous equipment cleaning and/or replacement performed in accordance with 261.35 and occurred after cessation of chlorophenolic preservative use	92	261.35(b)(4)(i)					
documentation that must be maintained as part of the facility's operating record	82	261.35(c)					
name and address of the facility	82	261.35(c)(1)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
formulations previously used and the date on which their use ceased in each process at the plant	82	261.35(c)(2)					
formulations currently used in each process at the plant	82	261.35(c)(3)					
equipment cleaning or replacement plan	82	261.35(c)(4)					
name and address of any persons who conducted the cleaning and replacement	82	261.35(c)(5)					
dates on which cleaning and replacement were accomplished	82	261.35(c)(6)					
dates of sampling and testing	82	261.35(c)(7)					
description of sample handling and preparation techniques	82	261.35(c)(8)					
description of the tests performed, the date, and the results of the tests	82	261.35(c)(9)					
name and model numbers of the instrument(s) used in performing the tests	82	261.35(c)(10)					
QA/QC documentation	82	261.35(c)(11)					
signed certification statement	82	261.35(c)(12)					

					LESS STRIN- TO GENT  3-cd)pyrene, ibenzo-p-dioxin	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	STRIN-	MORE STRIN- GENT	BROADER IN SCOP
		APPENDIX III TO	PART 261				
CHEMICAL ANALYSIS	TEST MET	HODS					
add the compound, "Benzo(k) fluoranthene", in alphabetical order, to Table 1	82	Table 1, Appendix					
	0	TABLE 1 ANALYSIS M RGANIC CHEMICALS CON					
	Compound		Method N	los.			
		* * * *	* * *				
	Benzo(k) flu	oranthene	8100,8250,827	0,8310			
		* * * *	* * *				
		APPENDIX VII TO	PART 261				
BASIS FOR LISTING HA	AZARDOUS	WASTE	_				1
add "F032", "F034", and "F035" to list in alphanumeric order as shown below:	82	Appendix VII					
EPA hazardous waste No.			rdous constituents or which listed				•
*	*	*	*	*		*	•
F032	pentachloroph	acene, benzo(a)pyrene, diben nenol, arsenic, chromium, tetr hexa-, heptachlorodibenzofu	a-, penta-, hexa-, hepta			S,	
				( - 1 · ) (1 · · · -			
F034		acene, benzo(k)fluoranthene, cd)pyrene, naphthalene, arse		(a,n)antnra	cene,		
F034		cd)pyrene, naphthalene, arse		:(a,n)antnra	cene,		

		as of June 30, 1997	(cont'd)				
					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADEI IN SCOP
		APPENDIX VIII T	O PART 261				
HAZARDOUS CONSTIT	TUENTS					_	
add the specified hazardous constituents in alphabetical order as shown below:	82	Appendix VIII					
	Chemical Chemical abstracts abstracts Hazardous name No. waste No.						
Benzo(k)fl	* uoranthene *	* * * *	* * * * Same 207-0	98-9			
Heptachlo Heptachlo	rodibenzofurans rodibenzo-p-diox *		· · · · · · · · · · · · · · · · · · ·			_	
PART 262 - ST	ANDARDS	APPLICABLE TO G	ENERATORS OF	HAZAR	RDOUS V	VASTE	
	SUBPAR	RT C - PRE-TRANSPO	ORT REQUIREM	ENTS			
ACCUMULATION TIME	E						
the waste is placed:	92	262.34(a)(1)					
in containers and generator complies with Subpart I of Part 265; and/or	92	262.34(a)(1)(i)					
in tanks and generator complies with Subpart J of Part 265, except 265.197(c) and 265.200; and/or	92	262.34(a)(1)(ii)					
on drip pads and							

262.34(a)(1)(iii)

generator complies with Subpart W of Part 265 and maintains following

82,92

records:

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
†,9	description of procedures to ensure all wastes are removed from drip pad and associated collection system at least once every 90 days	82,92	262.34(a)(1)(iii)(A)					
†,9	documentation of each waste removal, including quantity, date and time of removal; generator exempt from Subparts G and H of Part 265, except 265.111 and 265.114	82,92	262.34(a)(1)(iii)(B)					
9	date each period of accumulation begins is marked and visible	82,92	262.34(a)(2)					

PART 264 - STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE AND DISPOSAL FACILITIES

# APPLICABILITY add reference to paragraph (c) add new paragraph subjecting tanks, sumps and other collection devices used in conjunction with Subpart W-regulated drip pads to Part 264, Subpart J requirements 82 SUBPART J - TANK SYSTEMS 264.190 264.190

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
10			SUBPART W - DI	RIP PADS				
	APPLICABILITY							
	Subpart W applies to owners and operators of facilities that use new or existing drip pads to convey treated wood drippage, precipitation, and/or surface water runoff to an associated collection system; existing drip pads defined; applicability of 264.573(b)(3) leak collection system requirement	82,92,120	264.570(a)					
	owner or operator of certain drip pads inside or under a structure not subject to 264.573(e) or 264.573(f) regulations, as appropriate	82,92	264.570(b)					
	Subpart W requirements not applicable to management of infrequent, incidental drippage in storage yards provided:	120	264.570(c)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	owner or operator maintains and complies		264.570(c)(1)					
	with a written contingency plan describing how owner or		264.570(c)(1)(i)					
	operator will respond immediately to discharge of infrequent and		264.570(c)(1)(ii)					
	incidental drippage; at a minimum, what the		264.570(c)(1)(iii)					
	contingency plan must describe	120	264.570(c)(1)(iv)					
	ASSESSMENT OF EXIST	TING DRIP	PAD INTEGRITY		ı		1	
	evaluation of existing drip pads; by June 6, 1991, written assessment obtained and kept on file; annual review, update and recertification required until 264.573 standards are met, except 264.573(b) standards for liners and leak detection systems	82,92,120	264.571(a)					
11, 12	development of written plan for upgrading, repairing and modifying drip pad to meet 264.573(b) requirements; submittal of plan to Regional Administrator no later than 2 years before completion of modifications; written plan documentation, review and certification requirements	82,92,120	264.571(b)					

						STATE ANALOG IS:		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
12			264.571(b)(1)					
			264.571(b)(2)					
	removed	82,120	264.571(b)(3)					
	submittal of required drawings and certification to Regional Administrator or State Director upon completion of all upgrades, repairs, and modifications	82,92	264.571(c)					
	if drip pad found to be leaking or unfit for use, compliance with 264.573(m) provisions or close drip pad in accordance with 264.575	82,92	264.571(d)					
13	DESIGN AND INSTALL	ATION OF	NEW DRIP PADS					
	owners and operators of new drip pads must ensure that the pads are designed, installed and operated in accordance with one of the following:	82,92,120	264.572					
	all of the requirements of 264.573 (except 264.573(a)(4)), 264.574 and 264.575	120	264.572(a)					
	all of the requirements of 264.573 (except 264.573(b)), 264.574 and 264.575	120	264.572(b)					
13	DESIGN AND OPERATI	NG REQUII	REMENTS					
	drip pads must:	82,92	264.573(a)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
be constructed of non- earthen materials, excluding wood and non- structurally supported asphalt	82,92	264.573(a)(1)					
be sloped for free- drainage to the associated collection system	82,92	264.573(a)(2)					
have a curb or berm around the perimeter	82,92	264.573(a)(3)					
hydraulic conductivity requirements; maintain surface free of cracks and gaps; sealing material must be chemically compatible with preservatives that contact pad; requirements apply to existing drip pads and drip pads of owners/operators electing to comply with 264.572(a)	82,92,120	264.573(a)(4)(i)					

						CTATE A	NALOGIS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
14	owner or operator must obtain and keep at the facility written assessment of drip pad certified by independent qualified registered engineer; assessment must attest to results of evaluation; assessment must be reviewed, updated and recertified annually; evaluation must document extent to which drip pad meets 264.573 (except 264.573(b)) design and operating standards	120	264.573(a)(4)(ii)					
17	remove notes regarding administrative stays for new and existing drip pads	†91,92, †101,120	264.573(a)(4)/notes					
18	be of sufficient structural strength and thickness to meet specified conditions	82,92	264.573(a)(5)					
19	if owner/operator elects to comply with § 264.572(b) instead of § 264.572(a), the drip pad must have:	82,92,120	264.573(b)					
	a synthetic liner that meets certain design, construction and installation specifications	82,92	264.573(b)(1)					
	specific requirements for liner construction materials	82,92	264.573(b)(1)(i)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
foundation or base requirements	82,92	264.573(b)(1)(ii)					
liner must cover all surrounding earth that could come into contact with the waste or leakage	82,92	264.573(b)(1)(iii)					
leakage detection system immediately above the liner; detection system must be:	82,92	264.573(b)(2)					
constructed of materials that are:	82,92	264.573(b)(2)(i)					
chemically resistant to relevant waste and leakage	82,92	264.573(b)(2)(i)(A)					
of sufficient strength and thickness to prevent collapse	82,92	264.573(b)(2)(i)(B)					
designed and operated to function without clogging through the scheduled closure of the drip pad; and	82,92	264.573(b)(2)(ii)					
designed to detect drip pad failure or the release of hazardous waste or accumulated liquid at the earliest practicable time	82,92	264.573(b)(2)(iii)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
leakage collection system immediately above the liner designed, constructed, maintained and operated to collect leakage from below the drip pad; date, time and quantity of leakage collected must be documented in operating log	120	264.573(b)(3)					
maintenance of drip pads; note regarding remedial action	82,92	264.573(c)					
convey, drain, and collect liquid resulting from drippage or precipitation in order to prevent run- off	82,92	264.573(d)					
run-on control system requirements	82,92	264.573(e)					
run-off management system requirements, unless system is protected by a structure, as described in 264.570(b)	82,92	264.573(f)					
evaluation of drip pad for compliance with 264.573(a)-(f) requirements; design certification required	82,92	264.573(g)					

-					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
removal of drippage and accumulated precipitation from associated collection system as necessary to prevent overflow onto the drip pad	82,92	264.573(h)					
thorough cleaning of drip pad surface in a manner and frequency to meet specified conditions; documentation of date, time and cleaning procedure in facility's operating log; owner/ operator must determine whether residues are hazardous under 262.11 and, if so, manage them according to Parts 261- 268, 270 and RCRA §3010	82,92,120	264.573(i)					
minimize tracking of hazardous waste or constituents off the drip pad	82,92	264.573(j)					
after removal from treatment vessel, treated wood from pressure and non-pressure processes must be held on pad until drippage has ceased; documentation required	82,92	264.573(k)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
collection and holding units for run-on and run- off control systems emptied or otherwise managed as soon as possible after storms to maintain design capacity	82,92	264.573(1)					
throughout the active life of the drip pad and as specified in the permit, repair of detected condition that may have caused or has caused a release of hazardous waste within a reasonable period of time, in accordance with the following procedures:	82,92	264.573(m)					
upon detection of a condition that may have caused or has caused a release of hazardous waste, the owner must:	82,92	264.573(m)(1)					
enter discovery in the facility operating log	82,92	264.573(m)(1)(i)					
immediately remove from service affected portion of drip pad	82,92	264.573(m)(1)(ii)					
determine steps to repair drip pad and clean up any leakage; establish schedule for repairs	82,92	264.573(m)(1)(iii)					

						CTATE A	NALOCIC.	
							NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	notify Regional Administrator within 24 hours after discovery; provide written notice as specified within 10 working days	82,92	264.573(m)(1)(iv)					
	review, determination and notification by Regional Administrator	82,92	264.573(m)(2)					
20	written notification to Regional Administrator and certification of compliance with 264.573(m)(1)(iv) after repairs and clean up	82,92	264.573(m)(3)					
	should a permit be necessary, Regional Administrator will specify in the permit all design and operating practices necessary to ensure that 264.573 requirements are met	82,92	264.573(n)					
	documentation in operating log, as specified, of past operating and waste handling practices	82,92	264.573(o)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
13	INSPECTIONS							
	inspection of liners and cover systems for uniformity, damage and imperfections during construction or installation; inspection and certification of liners to meet 264.573 requirements; maintenance of certification as part of the facility operating record; inspection of liners and covers after installation	82,92	264.574(a)					
	drip pad must be inspected weekly and after storms to detect evidence of any of the following:	82,92	264.574(b)					
	deterioration, malfunctions or improper operation of run-on and run-off control systems	82,92	264.574(b)(1)					
	presence of leakage in and proper functioning of leak detection system	82,92	264.574(b)(2)					
	deterioration or cracking of drip pad surface; note regarding remedial action	82,92	264.574(b)(3)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
13	CLOSURE							
	at closure, removal and decontamination requirements; management as hazardous waste	82,92	264.575(a)					
	conditions under which owner or operator must close facility and perform post-closure care in accordance with 264.310 requirements; for permitted units, permit requirement continues throughout post-closure period; drip pad is considered a landfill and must meet Subparts G and H requirements of Part 264	82,92	264.575(b)					
	owner or operator of an existing drip pad that does not comply with the 264.573(b)(1) liner requirements must:	82,92	264.575(c)(1)					
	include in closure plans for drip pad under 264.112, a plan for 264.575(a) compliance and a contingent plan for 264.575(b) compliance	82,92	264.575(c)(1)(i)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
prepare a contingent post-closure plan under 264.118 for complying with 264.575(b) in case not all contaminated subsoils can be practicably removed at							
closure	82,92	264.575(c)(1)(ii)					
cost estimates calculated under 264.112 and 264.144 for closure and post-closure care of drip pad subject to 264.575(c) must include the cost of complying with the contingent closure plan and the contingent post-closure plan; cost of expected closure under 264.575(a) need not be included	82,92	264.575(c)(2)					

PART 265 - INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE AND DISPOSAL FACILITIES

#### SUBPART J - TANK SYSTEMS APPLICABILITY add reference to 82 265.190 paragraph (c) add new paragraph subjecting tanks, sumps and other collection devices used in conjunction with Subpart W-regulated drip pads to Part 265, Subpart J 82 265.190(c) requirements

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
		SUBPART W - DI	RIP PADS				
APPLICABILITY							
Subpart W applies to owners and operators of facilities that use new or existing drip pads to convey treated wood drippage, precipitation, and/or surface water runoff to an associated collection system; existing drip pads defined; applicability of 265.443(b)(3) leak collection system requirement	82,92,120	265.440(a)					
owner or operator of certain drip pads inside or under a structure not subject to 265.443(e) or 265.443(f) regulations, as appropriate	82	265.440(b)					
Subpart W requirements not applicable to management of infrequent, incidental drippage in storage yards provided:	120	265.440(c)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	wner or operator aintains and complies		265.440(c)(1)					
co	ith a written ontingency plan		265.440(c)(1)(i)					
op	escribing how owner or perator will respond to scharge of infrequent		265.440(c)(1)(ii)					
an	a minimum, what the		265.440(c)(1)(iii)					
	ontingency plan must escribe	120	265.440(c)(1)(iv)					
A	SSESSMENT OF EXIST	ΓING DRIP	PAD INTEGRITY					
dr 19 ob an an rec sta fo	valuation of existing rip pads; by June 6, 291, written assessment otained and kept on file; anual review, update and recertification equired until 265.443 andards are met, except or 265.443(b) standards or liners and leak etection systems	82,120	265.441(a)					
plane rej dr 26 su Re no be mo plane re	evelopment of written an for upgrading, pairing and modifying rip pad to meet 65.443(b) requirements; abmittal of plan to egional Administrator o later than 2 years efore completion of odifications; written an documentation, eview and certification quirements	82,120	265.441(b)					

						STATE ANALOG IS:		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
21			265.441(b)(1)					
			265.441(b)(2)					
	removed	82,120	265.441(b)(3)					
	submittal of required drawings and certification to Regional Administrator or State Director upon completion of all repairs and modifications	82	265.441(c)					
	if drip pad found to be leaking or unfit for use, comply with 265.443(m) provisions or close drip pad in accordance with 265.445	82	265.441(d)					
	DESIGN AND INSTALL							
	owners and operators of new drip pads must ensure that the pads are designed, installed and operated in accordance with one of the following:	82, 120	265.442					
	all of the applicable requirements of 265.443 (except 265.443(a)(4)), 265.444 and 265.445	120	265.442(a)					
	all of the applicable requirements of 265.443 (except 265.443(b)), 265.444 and 265.445	120	265.442(b)					
	DESIGN AND OPERATI	NG REQUI	REMENTS	,				
	drip pads must:	82	265.443(a)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	be constructed of non- earthen materials, excluding wood and non- structurally supported asphalt	82	265.443(a)(1)					
	be sloped to free-drain wastes to the associated collection system	82	265.443(a)(2)					
	have a curb or berm around the perimeter	82	265.443(a)(3)					
22, 23	hydraulic conductivity requirements; maintain surface free of cracks and gaps; surface material must be chemically compatible with preservatives that contact pad; requirements apply to existing drip pads and drip pads of owners/ operators electing to comply with 265.442(a)	82,120	265.443(a)(4)(i)					
22	owner or operator must obtain and keep at the facility a written assessment of drip pad certified by independent qualified registered engineer; assessment must attest to results of evaluation; assessment must be reviewed, updated and recertified annually; evaluation must document extent to which drip pad meets 265.443 (except 265.443(b)) design and operating standards	120	265.443(a)(4)(ii)					

						STATE ANALOG IS:		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
24	remove notes regarding administrative stays for new and existing drip pads	†91, †101,120	265.443(a)(4)/notes					
	be of sufficient structural strength and thickness to meet specified conditions; note regarding structural integrity standards	82	265.443(a)(5)					
25	if an owner/operator elects to comply with § 265.442(b) instead of § 265.442(a), the drip pad must have:	82,120	265.443(b)					
	a synthetic liner that meets certain specifications	82	265.443(b)(1)					
	specific requirements for liner construction materials	82	265.443(b)(1)(i)					
	foundation or base requirements	82	265.443(b)(1)(ii)					
	liner must cover all surrounding earth that could come into contact with the waste or leakage	82	265.443(b)(1)(iii)					
	leakage detection system immediately above the liner; detection system must be:	82	265.443(b)(2)					
	constructed of materials that are:	82	265.443(b)(2)(i)					
	chemically resistant to relevant waste and leakage	82	265.443(b)(2)(i)(A)					

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	of sufficient strength and thickness to prevent collapse	82	265.443(b)(2)(i)(B)					
26	designed and operated to function without clogging through scheduled drip pad closure	92	265.443(b)(2)(ii)					
26	designed to detect the failure of the drip pad or the presence of hazardous waste release or accumulated liquid at the earliest practicable time	82,92	265.443(b)(2)(iii)					
	leakage collection system immediately above the liner designed, constructed, maintained and operated to collect leakage from below the drip pad for removal; date, time and quantity of leakage collected must be documented in operating log	120	265.443(b)(3)					
	maintenance of drip pads; note regarding remedial action	82	265.443(c)					
	convey, drain, and collect liquid resulting from drippage or precipitation in order to prevent run- off	82	265.443(d)					
	run-on control system requirements, unless drip pad is protected by a structure, as described in 265.440(b)	82	265.443(e)					

					STATE ANALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
run-off management system requirements, unless drip pad is protected by a structure, as described in 265.440(b)	82	265.443(f)					
evaluation of drip pad for compliance with 265.443(a)-(f) requirements; design certification required	82	265.443(g)					
removal of drippage and accumulated precipitation from associated collection system as necessary to prevent overflow onto the drip pad	82	265.443(h)					
thorough cleaning of drip pad surface in a manner and frequency to meet specified conditions; documentation of date, time and cleaning procedure in facility's operating log	82,120	265.443(i)					
minimize tracking of hazardous waste or constituents off the drip pad	82	265.443(j)					
after removal from treatment vessel, treated wood from pressure and non-pressure processes must be held on pad until drippage has ceased; documentation required	82	265.443(k)					

-					STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP	
collection and holding units for run-on and run- off control systems emptied or otherwise managed as soon as possible after storms to maintain design capacity	82	265.443(1)						
throughout the active life of the drip pad and as specified in the permit, repair of detected condition that may have caused or has caused a release of hazardous waste within a reasonable period of time, in accordance with the following procedures:	82,92	265.443(m)						
upon detection of a condition that may have caused or has caused a release of hazardous waste, the owner must:	82,92	265.443(m)(1)						
entry of discovery in the facility operating log	82	265.443(m)(1)(i)						
immediate removal from service of affected portion of drip pad	82	265.443(m)(1)(ii)						
determination of steps to repair drip pad, remove any leakage, and establish schedule for clean up and repairs	82	265.443(m)(1)(iii)						

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
	notify Regional Administrator within 24 hours after discovery; provide written notice as specified within 10 working days	82	265.443(m)(1)(iv)					
	review, determination and notification by Regional Administrator	82	265.443(m)(2)					
27	written notification to Regional Administrator and certification of compliance with 265.443(m)(1)(iv) after repairs and clean up	82,92	265.443(m)(3)					
	documentation in operating log, as specified, of past operating and waste handling practices	82	265.443(n)					
	INSPECTIONS							
	inspection of liners and cover systems for uniformity, damage and imperfections during construction or installation; inspection and certification of liners to meet 265.443 requirements; maintenance of certification as part of the facility operating record; inspection of liners and covers after installation	82	265.444(a)					

				STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
drip pad must be inspected weekly and after storms to detect evidence of any of the following:	82	265.444(b)					
deterioration, malfunctions or improper operation of run-on and run-off control systems	82	265.444(b)(1)					
presence of leakage in and proper functioning of leak detection system	82	265.444(b)(2)					
deterioration or cracking of drip pad surface; note regarding remedial action	82	265.444(b)(3)					
CLOSURE						1	•
at closure, removal and decontamination requirements; management as hazardous waste	82	265.445(a)					
closure and post-closure care of drip pad as a landfill under 265.310, if some contaminated subsoils cannot be removed or decontaminated; for permitted units, permit requirement continues throughout post-closure period	82	265.445(b)					
owner or operator of an existing drip pad not in compliance with the 265.443(b)(1) liner requirements must:	82	265.445(c)(1)					

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
include in the closure plan for the drip pad under 265.112, a plan for 265.445(a) compliance and a contingent plan for 265.445(b) compliance	82	265.445(c)(1)(i)					
prepare contingent post- closure plan under 265.118 for complying with 265.445(b) in case not all contaminated subsoils can be practicably removed at closure	82	265.445(c)(1)(ii)					
cost estimates calculated under 265.112 and 265.144 for closure and post-closure care of drip pad subject to 265.445(c) must include cost of complying with contingent closure plan and contingent post-closure plan; cost of expected closure under 265.445(a) need not be included	82	265.445(c)(2)					

					STATE A	NALOG IS:	
					LESS	MORE	
	CHECKLIST		ANALOGOUS STATE	EQUIV-	STRIN-	STRIN-	BROADER
FEDERAL REQUIREMENTS	REFERENCE	FEDERAL RCRA CITATION	CITATION	ALENT	GENT	GENT	IN SCOP

#### PART 270 - EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT PROGRAM

#### SUBPART B - PERMIT APPLICATION

-		DEFART B - FERMIT AFFEICATION						
SPECIAL PART B INFORMATION REQUIREMENTS FOR DRIP PADS								
additional information to be provided by owners and operators of hazardous waste treatment, storage, or disposal facilities that collect, store, or treat hazardous waste on drip pads, except as otherwise provided by 264.1	82	270.26						
list of hazardous wastes placed or to be placed on each drip pad	82	270.26(a)						
detailed plans and an engineering report describing how 264.90(b) (2) will be met, if an exemption is sought to Subpart F of Part 264	82	270.26(b)						
detailed plans and an engineering report describing the design, construction, operation and maintenance of drip pad to meet 264.573 requirements; submission must address 264.571 items	82,92	270.26(c)						
design characteristics of the drip pad	82	270.26(c)(1)						
liner system	82	270.26(c)(2)						

					STATE ANALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
leakage detection system	82	270.26(c)(3)					
practices designed to maintain drip pads	82	270.26(c)(4)					
associated collection system	82	270.26(c)(5)					
control of run-on to the drip pad	82	270.26(c)(6)					
control of run-off from the drip pad	82	270.26(c)(7)					
removal intervals and demonstration of sufficiency to prevent overflow	82	270.26(c)(8)					
procedures for cleaning drip pad at least once every seven days; provisions for documentation of date, time and cleaning procedure	82	270.26(c)(9)					
operating practices and procedures to minimize tracking of hazardous waste or waste constituents off the drip pad	82	270.26(c)(10)					
procedures for ensuring that treated wood from pressure and non-pressure processes is held on the drip pad until drippage has ceased; recordkeeping practices	82	270.26(c)(11)					

				STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADER IN SCOP
provisions for ensuring that collection and holding units for run-on and run-off control systems are emptied or managed as soon as possible after storms to maintain design capacity	82	270.26(c)(12)					
if treatment is carried out on the drip pad, details of process equipment used, and the nature and quality of residuals	82	270.26(c)(13)					
description of drip pad inspections to meet 264.573 requirements; include in 270.14(b)(5) inspection plan	82,92	270.26(c)(14)					
certification that drip pad design meets 264.573(a)- (f) requirements	82,92	270.26(c)(15)					
description of removal procedures at closure under 264.575(a); for waste not removed at closure, submittal of detailed plan and engineering report to describe compliance with 264.310(a) and (b); information should be included in closure plan and, where applicable, 270.14(b)(13) post-closure plan	82,92	270.26(c)(16)					

<sup>&</sup>lt;sup>1</sup> 261.4(a)(9)(i) was originally 261.4(a)(9) on Revision Checklist 82. Revision Checklist 92 redesignated it as 261.4(a)(9)(i) and added a new paragraph designated as 261.4(a)(9)(ii).

- Note the <u>Federal Register</u> 56 <u>FR</u> 27332 (June 13, 1991; Revision Checklist 91) incorrectly refers to 261.31 rather than to 261.31(a) as the place where the list of hazardous wastes from non-specific sources can be found. Revision Checklist 81 redesignated 261.31 as 261.31(a) and added 261.31(b).
- Waste codes F032, F034, and F035 were added to the table in 261.31(a) by Revision Checklist 82. Revision Checklist 91 (56 FR 27332; June 13, 1991) addressed an administrative stay of these listings. Revision Checklist 120 (57 FR 61492; December 24, 1992) terminated the June 13, 1991 administrative stay by amending the listings. For the States that did not adopt the June 13, 1991 administrative stay, the Revision Checklist 120 changes to these listings represent a narrowing of the F032, F034, and F035 listings. Thus, the Revision Checklist 120 changes are optional for States that did not adopt the administrative stay. For those States that did adopt the June 13, 1991 administrative stay, the wording added by the stay (i.e., the parenthetical note concerning the stay) should be removed and replaced with the wording presented in the December 24, 1992 rule (Revision Checklist 120) and in this consolidated checklist.
- Only those States that added the administrative stay addressed by the June 13, 1992 rule (56 <u>FR</u> 27332; Revision Checklist 91) to their code need to make the Revision Checklist 120 (57 <u>FR</u> 61492; December 24, 1992) change. Note that, although Revision Checklist 120 removed this footnote, this change was not included in the July 1, 1993 and 1994 CFRs. The rule addressed by Revision Checklist 144 (60 <u>FR</u> 33912; June 29, 1995) corrects the CFR error.
- Revision Checklist 82 originally introduced §261.35 into the code. Revision Checklist 92 made extensive formatting and word changes to 261.35(b).
- There is a typographical error in the July 1, 1991, rule (56 <u>FR</u> 30192; Revision Checklist 92). In 261.35(b)(1)(iii), "preservations," at the end of the sentence, should be "preservatives." The CFR has reflected this error since July 1, 1992. The correct word is included on this checklist.
- Note Revision Checklist 82 redesignated 262.34(a)(2)-(4) as 262.34(a)(3)-(5). Revision Checklist 92 changed these paragraphs back to their original numbering, i.e., 262.34(a)(2)-(4). Because these two changes cancelled each other out, they were not directly addressed by this checklist.
- The technical correction for §262.34, 56 <u>FR</u> 30192 (July 1, 1991; Revision Checklist 92), contains the text of the introductory paragraph, 262.34(a). As no revisions were made to this paragraph, it has not been included in this consolidated checklist. Also, because this technical correction made extensive changes to this section of the code, the "Federal Requirements" column summarizes the requirements rather than the changes.
- An error in the July 1, 1991, and 1992 <u>CFR</u>s makes it appear that there are two paragraphs designated as 262.34(a)(2) (see the editorial note in the <u>CFR</u>). Revision Checklist 82 inserted new text at 262.34(a)(2) and (a)(2)(i)-(ii) and redesignated the old 262.34(a)(2)-(4) as 262.34(a)(3)-(5). However, Revision Checklist 92 redesignated 262.34(a)(3)-(5) as 262.34(a)(2)-(4), returning the code to its original numbering and effectively removing the text at 262.34(a)(2) and incorporating these requirements into 262.34(a)(1) at 262.34(a)(1)(iii) and (iii)(A)&(B). It was not the Agency's intent to include these requirements both at 262.34(a)(1)(iii)(A)&(B) and at 262.34(a)(2) as is indicated in the July 1, 1991 and 1992 <u>CFR</u>s. The first 262.34(a)(2) in that <u>CFR</u> should not be in the code. This error was corrected by Revision Checklist 109 (57 FR 37194).
- The entire text of Subpart W of Part 264 was printed in the <u>Federal Register</u> (56 <u>FR</u> 30192; July 1, 1991) for Revision Checklist 92. This was done to demonstrate the numbering of each citation following the redesignation of sections to correspond with Subpart W, Part 265. Numerous paragraphs within the redesignated sections had no revisions made to them. Paragraphs in this consolidated checklist, where Revision

Checklist 92 is indicated in the "Checklist Reference" column, reflect revisions to wording, internal references, or numbering that were addressed in Revision Checklist 92.

- The <u>Federal Register</u> for Revision Checklist 92 (56 <u>FR</u> 30192; July 1, 1991) introduced a typographical error by incorrectly changing "in sufficient detail" to "insufficient detail". This typographical error was corrected by Revision Checklist 120 (57 FR 61492; December 24, 1992) to read "in sufficient detail".
- When this paragraph was revised by Revision Checklist 120, the instructions for revising it were unclear. According to EPA, the last sentence of 264.571(b), which introduces the subparagraphs, is to be removed, as well as subparagraphs (b)(1), (2), and (3). A technical correction will be published in the <u>Federal Register</u> in the near future.
- Revision Checklist 92 redesignated the original 264.575 (as introduced by Revision Checklist 82) as 264.572 and redesignated the original 264.572, 264.573 and 264.574 as 264.573, 264.574 and 264.575, respectively.
- This paragraph was originally introduced into the Federal code as 264.572(a)(4) by Revision Checklist 82 and redesignated as 264.573(a)(4) by Revision Checklist 92. Revision Checklist 120 completely revised the paragraph by removing the old 264.573(a)(4) and replacing it with 264.573(a)(4)(i) and 264.573(a)(4)(ii).
- There are two typographical errors in this paragraph in the <u>Federal Register</u> for Revision Checklist 120; in both occurrences, "1x10-7" should be "1x10-7." This error has been reflected in the CFR since July 1, 1993.
- Note that the <u>Federal Register</u> for Revision Checklist 120 is in error. According to EPA, the last line of 264.573(a)(4)(i) should read "§ 264.572(b) instead of § 264.572(a)" rather than "§ 264.572(a) instead of § 264.572(b)." As written, the code contradicts what is said in the 264.572(a)&(b) requirements.
- Note that there were two administrative stays at this citation. Revision Checklist 91 (56 FR 27332; June 13, 1991) added a note regarding an administrative stay with no ending date for new pads at 264.572(a)(4). However, 264.572(a)(4) was redesignated as 264.573(a)(4) by revision Checklist 92. Because of this redesignation, the Revision Checklist 91 administrative stay was incorrectly omitted in the July 1, 1991 and July 1, 1992 CFRs. Revision Checklist 101 (57 FR 5859; February 18, 1992) added a second note addressing an administrative stay for existing drip pads at wood preserving plants until October 31, 1992. These notes were removed by Revision Checklist 120 (57 FR 61492; December 21, 1992) when the administrative stays were terminated by the Federal Register for that checklist. This same Federal Register does not clearly indicate that these notes regarding administrative stays be removed; however, according to EPA, they should be removed. A technical correction will be published in the Federal Register in the near future.
- Note that a typographical error occurs in the text of 264.573(a)(5) in the <u>Federal Register</u> at 56 <u>FR</u> 30192 (July 1, 1991; Revision Checklist 92); "daily perations" should be "daily operations" as introduced into the code by Revision Checklist 82 (55 <u>FR</u> 50450; December 6, 1990). This error has been reflected in the CFR since July 1, 1992.
- There is an error in the <u>Federal Register</u> for Revision Checklist 120 at 264.573(b). According to EPA, the phrase "§ 264.572(b) instead of § 264.572(a)" likely should be "§ 264.572(a) instead of § 264.572(b)." As currently written, the code contradicts the 264.572(a)&(b) requirements.
- Note that paragraph 264.573(m)(3) was originally 264.572(m)(3) in the <u>Federal Register</u> at 55 <u>FR</u> 50450 (December 6, 1990; Revision Checklist 82). This paragraph had an incorrect reference; "paragraph (m)(3) of this section" should be "paragraph (m)(1)(iv) of this section." This error was addressed by the July 1, 1991 technical corrections to the rule (56 FR 30192; Revision Checklist 92).

- When this paragraph was revised by Revision Checklist 120, the instructions for revising it were unclear. According to EPA, the last sentence of 265.441(b), which introduces the subparagraphs, is to be removed, as well as subparagraphs (b)(1), (2), and (3). A technical correction will be published in the <u>Federal Register</u> in the near future.
- This paragraph was introduced into the Federal code by Revision Checklist 82 as 265.443(a)(4). Revision Checklist 120 completely revised the paragraph by removing the old 265.443(a)(4) and replacing it with 265.443(a)(4)(i) and 265.443(a)(4)(ii).
- Note that the <u>Federal Register</u> for Revision Checklist 120 is in error. According to EPA, the last line of 265.443(a)(4)(i) should read "\s 265.442(b) instead of \s 265.442(a)" rather than "\s 265.442(a) instead of \s 265.442(b)". As written, the code contradicts what is said in the 265.442(a)&(b) requirements.
- Revision Checklist 91 added a note regarding an administrative stay with no ending date for <u>new</u> drip pads. Revision Checklist 101 added a second note addressing an administrative stay for <u>existing</u> drip pads at wood preserving plants until October 31, 1992. These notes were removed by Revision Checklist 120 when the administrative stays were terminated by the <u>Federal Register</u> for that checklist. This same <u>Federal Register</u> does not clearly indicate that the notes regarding the administrative stays be removed; however, according to EPA, they should be removed. A technical correction will be published in the <u>Federal Register</u> in the near future.
- There appears to be an error in the <u>Federal Register</u> for Revision Checklist 120 at 265.443(b). The phrase "\$ 265.442(b) instead of \$ 265.442(a)" likely should be "\$ 265.442(a) instead of \$ 265.442(b)." As currently written, the code contradicts the 265.442(a)&(b) requirements.
- Revision Checklist 82 introduced the original 265.443(b)(2)(ii) into the code. Revision Checklist 92 redesignated the original 265.443(b)(2)(ii) as 265.443(b)(2)(iii) and added a new paragraph 265.443(b)(2)(ii).
- Note that 265.443(m)(3) in the <u>Federal Register</u> at 55 <u>FR</u> 50450 (December 6, 1990; Revision Checklist 82) has an incorrect reference. The reference to "paragraph (m)(3) of this section" should be to "paragraph (m)(1)(iv) of this section." This error was addressed by the July 1, 1991 technical corrections to the rule (56 FR 30192; Revision Checklist 92).
- Note that the "Special Part B Information Requirements for Drip Pads" was originally at 270.22 as introduced into the code by Revision Checklist 82. The Boilers and Industrial Furnaces rule (56 FR 7134; February 21, 1991; Revision Checklist 85) inadvertently removed section 270.22 from the code. The July 1, 1991 (56 FR 30192; Revision Checklist 92) Wood Preserving technical corrections notice rectified this problem by redesignating that section, as introduced by Revision Checklist 82, as 270.26.